

LWE SOFT MOUNT WASHER EXTRACTORS




EASY TO USE CONTROLLER



EASY TO USE DOOR HANDLE



SINGLE MOTOR DRIVE



SOFT MOUNT DESIGN

PERFECT FOR THOSE LOOKING FOR RELIABLE EQUIPMENT

THREE REASONS TO BUY

1. Affordable Soft Mount
2. Over 300+ G-force
3. Easy to Maintain



PEACE OF MIND

Each of our quality pieces have a one year guarantee from the date of purchase. One year limited parts warranty.

*Contact RAMCO for full details.

EXCELLENT FOR UPPER FLOOR INSTALLATIONS

FEATURES FOR OUR LWE SERIES

- Soft mount design allows for installation on upper floors
- Single Motor variable speed drive for optimized performance
- Easy to use microprocessor which has 30 programs
- Centrally located control panel for easy access to all components

DESCRIPTIONS	UNIT	LWE 60	LWE 110	LWE 180	LWE 230	LWE 275	LWE 350
RATED LOAD	LBS	60	110	180	230	275	350
CYLINDER SIZE	IN	30X22	38X28	48X28	48X34	48X41	52X43
WASHING SPEED	RPM	38	36	33	33	33	32
BALANCE SPEED	RPM	82	70	70	70	70	70
LOW/HIGH EXTRACT SPEED	RPM	255/850	235/750	235/670	235/650	235/660	235/660
G-FORCE	G	303	300	307	307	307	322
VARIABLE SPEED MOTOR	KW	3	4	6 1/2	7 1/2	11	18 1/2
HOT & COLD WATER INLETS	IN	3/4	1	1 1/2	1 1/2	1 1/2	1 1/2
WATER PRESSURE (RECOMMENDED)	PSI	30-50	30-50	30-50	30-50	30-50	30-50
STEAM INLET	IN	1/2	3/4	1	1	1	1
STEAM PRESSURE (RECOMMENDED)	PSI	50-75	50-75	50-75	50-75	50-75	50-75
AIR INLET	IN	N/A	1/2	1/2	1/2	1/2	1/2
AIR PRESSURE (RECOMMENDED)	PSI	N/A	50-75	50-75	50-75	50-75	50-75
DRAIN OUTLET	IN	3	4 1/2	5 1/2	5 1/2	5 1/2	5 1/2
DIMENSIONS (W X D X H)	IN	50X50X61	58X63X67	73X67X80	73X74X80	73X81X80	77X83X81
WEIGHT	LBS	2205	3528	5512	6614	7276	9921