

TRITON IRONER



FEATURES FOR OUR TRITON

Uses 1/3 less space than to a typical three roll ironer
 User friendly touch screen microprocessor
 Automatically controlled ironing speed per linen type
 Double chest heating provides triple pass to ensure a crisp, well-ironed result
 With a high ironing efficiency, the ironer is capable of speeds up to 97 feet per minute.

Finger bar guards ensure safety
 Hydraulic control system ensures safe and satisfying working conditions.
 Accudry technology, which adjusts the speed of the ironer dependent on the temperature of the chest, ensures sheets come out dry
 208-240/60/3 or 480/60/3 (must specify)

SINGLE ROLL, DOUBLE CHEST, TRIPLE PASS IRONER

DESCRIPTIONS	UNIT	
ROLL DIMENSION (DXL)	IN	33 X 130
IRONING SPEED	FT/MIN	16-98
VARIABLE SPEED MOTOR	KW	11
EXHAUST FAN MOTOR	KW	2.2
HYDRAULIC PUMP (UPPER CHEST)	KW	.55
HYDRAULIC PUMP (LOWER CHEST)	KW	.75
STEAM INLET	IN	1
STEAM RETURN	IN	3/4
STEAM PRESSURE (RECOMMENDED)	PSI	90 - 135
EXHAUST DIMENSION	IN	5 1/2
DIMENSIONS (LXWXH)	IN	194 X 65 X 59
MACHINE WEIGHT	LBS	14330